

SECURITY DOOR BR RC 2

RP100-KL2





Security door made of steel. Lightweight door panel construction BR RC 2 EN 1627.

Description The product has a smooth and stable finish and can be adapted

to most environments. Solid hinge with screwed fastening in door

leaf and in frame.

certificate. Adjustable bushings are included for easy installation.

Available in different frame and threshold finishes.

Mitred, bolted frame solution with double fixing points and option for removable threshold. Standard frame solution is delivered with integrated gasket groove and fixed threshold.

Materials Frames and door leaves are made of zinc -and aluminium coated

steel plates (galfan) with excellent corrosion resistance and good

adhesion to surface treatment

Stainless/acid resistant quality avaible

Finishes Original material (galfan) without painting and priming

Painted

Primed and painted

Hardware Locks, striking plates, door closers, bolts, cable conduits, etc. in

accordance with certification licence.

Door thickness 52.0 mm

Sheet thickness of door

leat

1.0 - 1.25 mm

Sheet thickness of door

frame

1.5 mm

Insulation 50.0 mm

Weight approx. 45 kg/m²

Fire rating A60, A90, A120

Burglary resistance Single leaf BR RC 2 NS EN1627

Double leaf BR RC 2 NS EN1627

Acoustic properties Up to 41 dB

Flexibility The products can be manufactured in the desired dimensions


and fitted with, or adapted for, special fittings related to evacua-

tions, break-ins, access control, etc.


This will entail restrictions in relation to the individual certificates.

Quality assurance In accordance with NS EN ISO 9001





THRESHOLD TYPES



FRAME DETAILS

