



RP100-KL3



Security door made of steel. Lightweight door panel construction BR RC 3 EN 1627.

Description	The product has a smooth and stable finish and can be adapted to most environments. Solid hinge with screwed fastening in door leaf and in frame.
Frame and threshold	The door is delivered with pre-Insulated frame in accordance with certificate. Adjustable bushings are included for easy installation. Available in different frame and threshold finishes. Mitred, bolted frame solution with double fixing points and option for removable threshold. Standard frame solution is delivered with integrated gasket groove and fixed threshold.
Materials	Frames and door leaves are made of zinc -and aluminium coated steel plates - Galfan with excellent corrosion resistance and good adhesion to surface treatment Stainless/acid resistant
Finishes	Original material (galfan) without painting and priming Painted Primed and painted
Hardware	Lock backsets, striking plates, door closers, bolts, cable conduits, etc. in accordance with certification licence.
Door thickness	52.0 mm
Sheet thickness of door leaf	1.25 mm
Sheet thickness of door frame	1.5 mm
Insulation	50.0 mm
Weight	approx. 48 kg/m ²
Fire rating	A60, A90, A120
Burglary resistance	Single leaf BR RC 3 NS EN1627
Acoustic properties	Up to 41 dB
Flexibility	The products can be manufactured in the desired dimensions and fitted with, or adapted for, special fittings related to evacuations, break-ins, access control, etc. This will entail restrictions in relation to the individual certificates.
Quality assurance	In accordance with NS EN ISO 9001

